



## GS 3/50 OPT

## GS 2/50 OPT

### EXCLUSIVE FEATURES

- ▶ INNOVATIVE GASKET
- ▶ INDEPENDENT MOTORS WITH LIGHT SWITCHES
- ▶ RELIABLE CONSTRUCTION FOR INTENSIVE USE
- ▶ DETACHABLE TANK AND SOLID CART
- ▶ MANUAL FILTER SHAKER
- ▶ DOUBLE STAGE MOTORS
- ▶ BIG AND BRAKED WHEELS
- ▶ STARSHAPED FILTER, PCB PREFILTER AND ADDITIONAL CARTRIDGE

Code	GS 2/50 OPT	GS 3/50 OPT
ASD015124	ASD015124	ASD015123
<b>TECHNICAL DATA</b>		
Usage	DRY	DRY
Number of phases	single phase	single phase
Voltage	220-240	220-240
N. and type of motor	2x2 stages	3x2 stages
Power	2000 - 2400 max	3000 - 3600 max
Water lift	2470	2470
Airflow	420	630
Tank Capacity	50	50
Diameter of inlet	60	60
Filtering surface	12000 + 2260	12000 + 2260
Sound Pressure Level	74	76
Dimensions (LxWxH)	580x700x1150	580x700x1150
Weight	64	66

### STANDARD EQUIPMENT

CODE: FTDP88585  
POLYESTER MAIN FILTER  
12.000 cm<sup>2</sup>



CODE: FTDP72142  
CARTRIDGE FILTER  
2260 cm<sup>2</sup>



CODE: FTDP00223  
POLYCARBON PREFILTER



### OPTIONAL ACCESSORIES

Basic tool kit Ø38-60 mm	PMDT00325
Anti-Static tool kit Ø38-60 mm	PMDT00326
Basic tool kit Ø50-60 mm	PMDT00443
Anti-Static tool kit Ø50-60 mm	PMDT00436