



IPC

BY TENNANT COMPANY

SCRUBBER DRYERS - WALK BEHIND

CT71

MAX PRODUCTIVITY

Up to
3150 m²/h

**BATTERIES
RUNNING TIME**

3,5 h standard

**WATER TANK
RUNNING TIME**

Up to **75'**
working session

TELEMATICS GPS (optional)
GEOLOCATION OF ALL YOUR MACHINES



MEMORY CARD



ANC™
ADVANCE NOISE CONTROL
54 dB IN ECO SELECT MODE



ORBITAL VERSION



ONE BRUSH VERSION



ROLLER VERSION



CERTIFICATIONS



GREEN CLEANING
EFFICIENCY



ISO 14067 CARBON
FOOTPRINT CERTIFIED

BATTERIES AND BATTERY CHARGER NOT INCLUDED

MOST FREQUENTLY USE

RETAIL



HORECA



CLEANING CONTRACTORS



MUNICIPALITIES



INNOVATIONS



INTER-
CHANGEABLE
BRUSH
HEAD



600 RPM
INTERCHANGEABLE
BRUSH HEAD



ORBITAL
BRUSH



DBL™
DOUBLE
BATTERY
LIFE



MEMORY
CARD



SLS™
SELF
LEVELING
SYSTEM



ECO
SELECT



SERVICE
MENU



HEPA
FILTER



ANTIBACTERIAL
PLASTIC


SPECS



ADJUSTABLE HANDLE FOR
A COMFORTABLE AND EASY
USE



FULL MACHINE CONTROL
THANKS TO AN INTUITIVE
CENTRAL KNOB



EASY ACCESS NO TOOLS

TECHNICAL DATA

WITH ELECTRIC TRACTION

		CT71 BT55	CT71 BT60	CT71 BT70	CT71 BT70 ANTIBACTERIAL
Code		LPTB01856	LPTB02919	LPTB01857	LPTB03426
PERFORMANCE					
Max theoretical productivity	m ² /h	2475	2700	3150	3150
Cleaning path	mm	550	600	700	700
Water tank capacity (solution recovery)	l	70/70	70/70	70/70	70/70
Max running time	min	210	210	210	210
Voltage	V-Ah	24	24	24	24
Installed power	W	1000	1400	1400	1400
Brush pressure	kg	18	23	23	23
Squeegee width	mm	815	815	940	940
Max speed	km/h	4,5	4,5	4,5	4,5
Weight (Without Batteries)	kg	92	95	99	99
Dimension (LxWxH)	mm	1327x563x1033	1279x653x1033	1297x753x1033	1297x753x1033

STANDARD EQUIPMENT

		CT71 BT55	CT71 BT60	CT71 BT70	CT71 BT70 ANTIBACTERIAL
BRUSHES					
PPL SOFT		SPPV01352	2xSPPV01473	2xSPPV01472	2xSPPV01472
SQUEEGEE BLADES					
LATEX FRONT BLADE		MPVR08039 - 880mm	MPVR08039 - 880mm	MPVR08040 - 1020mm	MPVR08040 - 1020mm
LATEX REAR BLADE		MPVR08035 - 900mm	MPVR08035 - 900mm	MPVR08036 - 1020mm	MPVR08036 - 1020mm

WITH ELECTRIC TRACTION AND ELECTRONIC BRUSH PRESSURE CONTROL

ROLLER - WITH ELECTRIC TRACTION AND ELECTRONIC BRUSH PRESSURE CONTROL

		CT71 XP60	CT71 XP70	CT71 XP55 R
Code		LPTB02921	LPTB01858	LPTB02927
PERFORMANCE				
Max theoretical productivity	m ² /h	2700	3150	2475
Cleaning path	mm	600	700	550
Water tank capacity (solution recovery)	l	70/70	70/70	70/70
Max running time	min	210	210	210
Voltage	V-Ah	24	24	24
Installed power	W	1450	1450	2350
Brush pressure	kg	31	31	18
Squeegee width	mm	815	940	815
Max speed	km/h	4,2	4,2	4,2
Weight (Without Batteries)	kg	96	99	104
Dimension (LxWxH)	mm	1279x653x1033	1297x753x1033	1288x640x1033

STANDARD EQUIPMENT

		CT71 XP60	CT71 XP70	CT71 XP55 R
BRUSHES				
PPL SOFT		2xSPPV01473	2xSPPV01472	-
CYLINDRICAL BRUSH - PPL SOFT Ø 0,3 mm		-	-	SPPV01163
SQUEEGEE BLADES				
LATEX FRONT BLADE		MPVR08040 - 1020mm	MPVR08040 - 1020mm	MPVR08039 - 880mm
LATEX REAR BLADE		MPVR08036 - 1020mm	MPVR08036 - 1020mm	MPVR06288 - 715mm

TECHNICAL DATA

600 RPM - WITH ELECTRIC TRACTION AND ELECTRONIC BRUSH PRESSURE CONTROL

Code	CT71 XP55 600 RPM		CT71 XP70 600 RPM
		LPTB02925	LPTB02926
PERFORMANCE			
Max theoretical productivity	m ² /h	2475	3150
Cleaning path	mm	550	700
Water tank capacity (solution recovery)	l	70/70	70/70
Max running time	min	210	210
Voltage	V-Ah	24	24
Installed power	W	1080	1480
Brush pressure	kg	18	23
Motor Brush RPM	rpm	600	600
Squeegee width	mm	815	940
Max speed	km/h	4,5	4,5
Weight (Without Batteries)	kg	89,9	95,4
Dimension (LxWxH)	mm	1327x563x1033	1297x753x1033

STANDARD EQUIPMENT

	CT71 XP55 600 RPM	CT71 XP70 600 RPM
PAD HOLDER		
MICROFIBER PAD	SPPV01978	SPPV01983
STANDARD - DIAMOND PAD	SPPV01335	SPPV01228
SQUEEGEE BLADES		
LATEX FRONT BLADE	MPVR08039 - 880mm	MPVR08040 - 1020mm
LATEX REAR BLADE	MPVR08035 - 900mm	MPVR08036 - 1020mm










ORBITAL WITH ELECTRIC TRACTION AND ELECTRONIC BRUSH PRESSURE CONTROL

Code	CT71 XP20" ORBITAL	
		LPTB01671
PERFORMANCE		
Max theoretical productivity	m ² /h	2794
Cleaning path	mm	500
Water tank capacity	l	70/70
Max running time	min	210
Voltage	V-Ah	24
Installed power	W	1030
Brush pressure	kg	45,7
Pad RPM	RPM	2200
Squeegee with	mm	815
Max speed	km/h	4,2
Weight	kg	108
Dimension (LxWxH)	mm	1225 x 512 x 1033

STANDARD EQUIPMENT

	CT71 XP20" ORBITAL
SQUEEGEE BLADES	
LATEX FRONT BLADE	MPVR08039 - 880mm
LATEX REAR BLADE	MPVR08035 - 900mm

OPTIONAL ACCESSORIES

	OPTIONAL	CODE	CT71 B55	CT71 BT55	CT71 BT60	CT71 BT70	CT71 XP60	CT71 XP70	CT71 XP55 600 RPM	CT71XP70 600 RPM	CT71 XP55 R	CT71XP20" ORBITAL
 	HEPA Filter	KTRI06666										
	Chem dose kit	KTRI04846	•	•	•	•	•	•	•	•	•	•
	Splash guard 50/55 cm	KTRI05244	•	•					•			•
	Splash guard 60 cm	KTRI05245			•		•			•		
	Splash guard 70 cm	KTRI05246				•		•				
	Tools bar	KTRI04848	•	•	•	•	•	•	•	•	•	•
	Auto-Refill System	KTRI04849	•	•	•	•	•	•	•	•	•	•
	External suction kit	KTRI02257	•	•	•	•	•	•	•	•	•	•

BATTERIES AND BATTERY CHARGERS

BATTERIES	N°	CHARACTERISTICS	DIMENSION	RUNNING TIME	BATTERY CHARGERS
IPC gel battery BAAC00105	2	12V 105 Ah (C5)	345x170x285	210 min	DBL on board high freq. 24V 13 Ah- KTRI04845 DBL stand alone high frequency BLS010 - BACA00133
EXIDE gel battery BAAC00024	2	12V 105 Ah (C5)	345x174x283	210 min	DBL on board high freq. 24V 13 Ah- KTRI04845 DBL stand alone high frequency BLS010 BACA00133
EXIDE gel battery BAAC00132	2	12V 76 Ah (C5)	330x171x236	150 min	DBL on board high freq. 24V 13 Ah- KTRI04845 DBL stand alone high frequency BLS010 BACA00133
Acid tubular plate BAAC00136	2	12V 85 Ah (C5)	308x175x225	150 min	DBL on board high freq. 24V 13 Ah- KTRI04845 DBL stand alone high frequency BLS010 BACA00133 Stand alone low frequency 24V 12 Ah BACA0060
Dry charge flate plate BAAC00009	2	12V 105 Ah (C5)	261x171x210	210 min	DBL on board high freq. 24V 13 Ah- KTRI04845 DBL stand alone high frequency BLS010 BACA00133 Stand alone low frequency 24V 12 Ah BACA0060
Acid tubular plate BAAC00070	2	12V 118 Ah (C5)	345x170x285	210 min	DBL on board high freq. 24V 13 Ah- KTRI04845 DBL stand alone high frequency BLS010 BACA00133 Stand alone low frequency 24V 12 Ah BACA0060

RECOMMENDED BATTERIES AND BATTERY CHARGER