

VACUUM CLEANERS - SPECIAL SOLUTIONS - FLOODED AREA EMPTYING

GS 1/41 SUB

NEW

POWER MAX

WATER LIFT

AIRFLOW

TANK CAPACITY

1200 2470

EXCLUSIVE FEATURES

- **AP TUBE**
- **INNOVATIVE GASKET**
- **STRONG HOOKS**
- **SEALANT FLOATER & INTEGRATED ANTIFOAM**
- RELIABLE CONSTRUCTION **FOR INTENSIVE USE**
- **SUBMERSIBLE PUMP**
- **DOUBLE STAGE MOTOR**



MOST FREQUENTLY USE

HO.RE.CA. & HEALTHCARE

AGRICULTURE

CONSTRUCTION

HARDWARE CUSTOMER

HEAVY INDUSTRY

INNOVATIONS



SPECS



SUBMERSIBLE PUMP



WATER FLOW VALVE



POWER SOCKET ON BOARD (FOR PUMP)

TECHNICAL DATA

		GS 1/41 SUB
Code		ASD013245
PERFORMANCE		
Usage		WET
Motor		1x2 stage
Power	W	1000-1200 max
Voltage	V	220-240
Water lift	mmH₂0	2470
Airflow	m³/h	210
Tank Capacity/Material	l	41/steel
Cable length	m	8,5
Sound Pressure Level (EN 60704-1; EN 60704-2-1; IEC 60335-2-69)	dB(A)	75
Pump type		Plastic
Pump power	kW	0,37
Pump capacity	l/min	180
Delivery head	m	7
Diameter of accessories	mm	38
Dimensions (LxWxH)	mm	380x380x900
Weight	kg	20,0

STANDARD EQUIPMENT

CODE:KTRI03856 - ACCESSORIES KIT Ø38 MM COMPOSED OF:

CODE: TBFX00393 FLEXIBLE HOSE 5 m Ø38 mm



CODE: LAFN43048 (FOR 1 PC) CODE: MPVR43047 ALUMINIUM/PLASTIC TUBE 50 cm Ø38 mm (MACHINE COMES WITH 2PCS)



HANDLE WITH AIR REGULATOR Ø38 mm



CODE: SPPV43051 WET TOOL Ø38 mm





CODE: SPPV43052 ROUND BRUSH Ø38 mm



CODE: MPVR43049 **ADAPTER**



OPTIONAL ACCESSORIES



To connect to water flow valve