



HIGH-PRESSURE WASHERS - HOT WATER (ELECTRIC BOILER)



PW-E100

ELECTRICALLY HEATED BOILER

PRESSURE

170

bar

FLOW RATE

600÷720

l/h

ABSORBED POWER

16,3÷35,7

kW

EXCLUSIVE CHARACTERISTICS

- ▶ DELAYED TOTAL STOP - DTS
- ▶ INTELLIGENT AUTOMATIC SWITCH OFF - IASF
- ▶ MICRO LEAKAGE CONTROL - MLC
- ▶ DRY RUNNING PROTECTION - DRP
- ▶ NOZZLE CLOGGING CONTROL - NCC
- ▶ WORKING HOURS COUNTER - WHC
- ▶ LIMESCALE/CORROSION PROTECTION UNIT - LCPU
- ▶ INTELLIGENT BOILER TEMPERATURE SETTING SYSTEM - ITSS
- ▶ ANTI-SCALE LEVEL CONTROL - ALC
- ▶ CHEMICAL LEVEL CONTROL - CLC
- ▶ FLOODING PREVENTION SYSTEM - FPS
- ▶ MAINTENANCE CHECK LED - MCL

- WITHOUT EXHAUST GAS
- GREATER EFFICIENCY WITHOUT USE FUEL



WITH NO-MARKING RUBBER WHEELS

MOST FREQUENTLY USE

INDUSTRY



AUTOMOTIVE



AGRICULTURE



MUNICIPALITIES



INNOVATIONS



G6000™
CERAMIC
TECH GUN



IPC
PUMP



MODULAR
BUILD-UP



MSCT™
MULTIFUNCTION
SAFETY
CONTROL



ALL
TERRAIN

SPECS



LARGE WHEELS IMPROVE MANEUVERABILITY AND EASE TRANSPORT.



22L DETERGENT TANK AND 25L ANTISCALE TANK.



3 STAGE HIGH EFFICIENCY BOILER WITH AISI 316 STAINLESS STEEL STRUCTURE.

TECHNICAL DATA

| Code | | PW-E100 D1710 P12 T IDAC41121 | PW-E100 D1712 P24 T IDAC41122 | PW-E100 D1712 P36 T IDAC41123 |
|--------------------------|-----------|-----------------------------------------|-----------------------------------------|-----------------------------------------|
| PERFORMANCE | | | | |
| Operating pressure | bar/Mpa | 30-170/3-17 | 30-170/3-17 | 30-170/3-17 |
| Flow rate | l/h | 450-600 | 450-720 | 450-720 |
| Outlet water temperature | °C | 70 | 70 | 70 |
| Power supply | Ph-V-Hz/A | 3-400-50/25 | 3-400-50/43,2 | 3-400-50/53 |
| Absorbed power | kW | 16,3 | 29 | 35,7 |
| Motor pole/rpm | | 4-1400 | 4-1400 | 4-1400 |
| Remote control | | DTS | DTS | DTS |
| Pump/head/pistons | | lpc plunger/brass/ceramic | lpc plunger/brass/ceramic | lpc plunger/brass/ceramic |
| Boiler thermal power | kW | 12 | 24 | 36 |
| Antiscale tank | l | 25 | 25 | 25 |
| Detergent tank | l | 22 | 22 | 22 |
| Detergent delivery | | high pressure | high pressure | high pressure |
| Dimension (LxWxH) | cm | 110x70x90 | 110x70x90 | 110x70x90 |
| Weight | Kg | 113 | 113 | 113 |

STANDARD EQUIPMENT

CODE: IPPR40025
HANDGRIP G6000



CODE: LCPR40087
EXTENSION P70 INOX



CODE: TBAP40237
NO-MARKING H.P HOSE
10 m 1/4"



CODE: UGLN49986
H.P. NOZZLE 1/4" 1504 -
(FOR 24kW/ 36kW)



CODE: UGLN11196
H.P. NOZZLE 1/4" 15035 -
(FOR 12kW)



OPTIONAL ACCESSORIES

CODE: LCPR29360
MUDGUARD LANCE - P90



CODE: LCPR24906
LANCE WITH DOUBLE
NOZZLE HOLDER - P70



CODE: SPID24939
FIXED HYDROBRUSH
LANCE P70



CODE: LCLC41140
LANCE FOR WASHING
FLOORS INOX



CODE: TBAP23853
DRAIN KIT 10 m



CODE: TBAP24406
DRAIN KIT 20 m



CODE: KTRI40341
HOSE REEL KIT



CODE: TBAP39122
NO-MARKING HIGH
PRESSURE HOSE 20 m



CODE: PRCH40040
10 Kg ANTI-SCALE TANK



CODE: KTRI40542
REMOTE CONTROL

