IPC

BY TENNANT COMPANY

PLANET 200S
PLANET 200 TS

Available 60Hz version

EXCLUSIVE FEATURES

▸ **INDEPENDENT MOTORS WITH LIGHT SWITCHES**
▸ **RELIABLE CONSTRUCTION FOR INTENSIVE USE**
▸ **DETACHABLE TANK AND SOLID CART**
▸ **MANUAL FILTER SHAKER**
▸ **TANGENTIAL OR METAL INLET**
▸ **DOUBLE STAGE MOTORS AND TURBINE**
▸ **BIG AND BRAKED WHEELS**
▸ **INDUSTRIAL FRAMEWORK WITH AISI 304 WITH DETACHABLE TANK**
▸ **TANGENTIAL INLET AND CONVEYOR CONE**
▸ **STARSHAPED FILTER, PCB PREFILTER AND ADDITIONAL CARTRIDGE**
▸ **VACUUM RELIEF VALVE AND FILTRATION LEVEL INDICATOR**
▸ **NON-SLIP NYLON WHEELS WITH BRAKES**

		PLANET 200S	PLANET 200 TS
Code		ASID00390	ASID89596
TECHNICAL DATA			
Usage		DRY	DRY
Number of phases		single phase	single phase
Voltage	V	220-240	220-240
Frequency	Hz	50-60	50-60
N. and type of motor		3x2 stages	3x3 stages
Power	W	3600-3800 max	4500 max
Water lift	mmH₂O	2795	3260
Airflow	m³/h	630	485
Tank Capacity	l	100	100
Diameter of inlet	mm	70	70
Filtering surface	cm²	19.500	19.500
Sound Pressure Level	dB(A)	76	76
Dimensions (LxWxH)	mm	660x900x1630	660x900x1630
Weight	kg	70	70

STANDARD EQUIPMENT

CODE: KTRI04597
FILTERING KIT

CODE: FTDP40014
POLYCARBON PREFILTER

OPTIONAL ACCESSORIES

Basic tool kit Ø50-70 mm	PMDT00444
Anti-Static tool kit Ø50-70 mm	PMDT00426
Anti-oil tool kit Ø50-70 mm	PMDT00448
Stainless steel float kit to recovery liquid (for Planet 100 lt)	KTRI03124
Hepa cartridge H13 kit 8.340 cm²	FTDP00800
Fixed accessory floor cleaning	SPPV49605
Steel grid and depressor kit for bag use	KTRI49559
Safe disposal polythene bag 0,1x80x100 mm	MISC00019
Star-shaped high temperature filter	KTRI04595

Information about waterlift and airflow refers to motors performances.
Specifications, descriptions and pictures are supplied as indicative: rights to technical modifications reserved without prior notice.