



IPC

BY TENNANT COMPANY

VACUUM CLEANERS - INDUSTRIAL SOLUTIONS - EXPLOSION PROOF



PLANET 1/50 OPT ATEX

CE EX II 3D Ex t IIIB T135°C Dc IP55

EXCLUSIVE FEATURES

- ▶ RELIABLE CONSTRUCTION FOR INTENSIVE USE
- ▶ DETACHABLE TANK AND SOLID CART
- ▶ MANUAL FILTER SHAKER
- ▶ BIG AND BRAKED WHEELS
- ▶ INDUSTRIAL FRAMEWORK WITH AISI 304 WITH DETACHABLE TANK
- ▶ STARSHAPED FILTER, PCB PREFILTER AND ADDITIONAL CARTRIDGE
- ▶ VACUUM RELIEF VALVE AND FILTRATION LEVEL INDICATOR
- ▶ LONG LASTING TURBINE WITH PERFECT PERFORMANCE
- ▶ EXPLOSION PROOF TURBINE AND DESIGN FOR ATEX ZONE 22
- ▶ CONDUCTIVE WHEELS WITH BRAKES
- ▶ STATIC DISSIPATING FILTERS
- ▶ GROUNDING SYSTEM

PLANET 1/50 OPT ATEX

ASID00697

Code		ASID00697
TECHNICAL DATA		
Usage		DRY
Number of phases		single phase
Voltage / Frequency	V	220-240/50
N. and type of turbine		1 x single stage
Power	W	1500
Water lift	mmH ₂ O	1800
Airflow	m ³ /h	220
Tank Capacity	l	50
Diameter of inlet	mm	60
Filtering surface	cm ²	12000
Sound Pressure Level	dB(A)	74
Dimensions (LxWxH)	mm	600x600x1600
Weight	Kg	65

STANDARD EQUIPMENT

CODE: KTRI03141
CONDUCTIVE
FILTERING KIT



CODE: FTDP00223
PCB PREFILTER



CODE: KTRI03681
HEPA H13 CARTRIDGE
KIT 3.080 cm²



OPTIONAL ACCESSORIES

Anti-Static tool kit Ø50-60 mm	PMDT00436
Anti-Static tool kit Ø38-60 mm	PMDT00326
Nylon filter for exhausting air	FTDP00410
Connection for nylon filter	RCVR00878
High Reach Cleaning ATEX	AVAILABLE