IPC

BY TENNANT COMPANY

GS 3/50 OPT W&D MFS

EXCLUSIVE FEATURES

- ▸ MODERN INDUSTRIAL DESING
- ▸ STRONG AND LIGHTWEIGHT TROLLEY WITH TOP MANUVRABILITY ON ANY TYPE OF FLOOR
- ▸ BIG RUBBER WHEELS WITH BREAKES
- ▸ DIMENSION COMPATIBLE WITH DOORS WIDTH
- ▸ 3 MOTORS WITH HIGHEST PERFORMANCE
- ▸ BEST SEALING OF THE POWERHEAD THANKS TO EXCLUSIVE BUILT-IN GASKET
- ▸ MODULAR CONFIGURATIONS TO COLLECT SOLID DIRECTLY IN THE TANK WITH A CYCLONIC CONVEYOR CONE, FINE DUST IN MICROFIBER BAG OF HIGH RESISTANCE OR LIQUID WITH A MECHANICAL STOP WHEN THE TANK IS FULL
- ▸ MANUAL FILTER SHAKER

		GS 3/50 OPT W&D MFS
Code		ASD013653
TECHNICAL DATA		
Usage		WET & DRY
Number of phases		single phase
Voltage / Frequency	V	220-240/50-60
N. and type of motor		3
Power	W	2900 - 3300 max
Water lift	mmH_2O	2560
Airflow	m^3/h	756
Tank Capacity	l	50
Diameter of inlet	mm	60
Filtering surface	cm^2	12.000 + 2.200
Sound Pressure Level	dB(A)	76
Dimensions (LxWxH)	mm	580x700x1150
Weight	Kg	68

STANDARD EQUIPMENT

CODE: FTDP88585
CLASS L STAR-SHAPED FILTER 12.000 cm^2

CODE: FTDP00223
PCB PREFILTER WITH CONDUCTIVE CARBON FOILS

CODE: FTDP00914
HEPA H14 CARTRIDGE 2.200 cm^2

CODE: -
CLASS M FLEECE BAG

CODE: PMVR06689
CONVEYOR CONE FOR CYCLONIC EFFECT AND FILTER PROTECTION

CODE: KTRI04157
FLOATING SYSTEM FOR LIQUID RECOVERY

OPTIONAL ACCESSORIES

Class M Star shaped filter 12.000 cm^2 resistant to 150°C	KTRI02483
Washable polyester cartridge (available as spare part) 3.000 cm^2	FTDP00583
Class M fleece bag -10 Pcs	KTRI05204
Mesh filter	FTDP28755
Fixing system for Mesh filter and cartridge	MPVR28723
Complete multipurpose premium tool kit 3 m ø38 mm	PMDT01227
Complete multipurpose premium tool kit 4 m ø50 mm	PMDT01228
Complete Oil&Abrasives Tool kit 4 m Ø38 mm	PMDT00928
Anti-Static tool kit Ø38-60 mm	PMDT00326

PLANET 150 S 3M

EXCLUSIVE FEATURES

- ▸ RELIABLE CONSTRUCTION FOR INTENSIVE USE
- ▸ DETACHABLE TANK AND SOLID CART
- ▸ MANUAL FILTER SHAKER
- ▸ BIG AND BRAKED WHEELS
- ▸ STARSHAPED FILTER, PCB PREFILTER AND ADDITIONAL CARTRIDGE
- ▸ TURBINE WITH PERFECT PERFORMANCE

		PLANET 150 S 3M
Code		ASID00374
TECHNICAL DATA		
Usage		DRY
Number of phases		single phase
Voltage	V	220-240
Motor		3
Power	W	3300
Water lift	mmH_2O	2470
Airflow	m^3/h	630
Tank Capacity	l	75
Diameter of inlet	mm	60
Filtering surface	cm^2	12.000
Sound Pressure Level	dB(A)	74
Dimensions (LxWxH)	mm	600x900x1500
Weight	Kg	62

STANDARD EQUIPMENT

CODE: KTRI02483
CLASS M STAR SHAPED FILTER 12.000 cm^2 RESISTANT TO 150°C

OPTIONAL ACCESSORIES

Basic tool kit Ø38-60 mm	PMDT00325
Anti-Static tool kit Ø38-60 mm	PMDT00326
Basic tool kit Ø50-60 mm	PMDT00443
Anti-Static tool kit Ø50-60 mm	PMDT00436
Fixed accessory floor cleaning	SPPV49605
PCB prefilter with conductive carbon foils	FTDP00223