



SCRUBBER DRIERS - WALK BEHIND

# CT40

MAX PRODUCTIVITY

2250 m<sup>2</sup>/h

BATTERIES  
RUNNING TIME

2,5 h

WATER TANK  
RUNNING TIME

45 min  
working session



## INNOVATIONS



DBL™  
DOUBLE  
BATTERY  
LIFE



SLS™  
SELF  
LEVELING  
SYSTEM

## SPECS



INTUITIVE CONTROL PANEL



ANTI-FOAM SYSTEM WITH  
SPECIAL ELECTROMECHANICAL  
SUCTION MOTOR PROTECTION

## MOST FREQUENTLY USED



RETAIL



HOSPITALITY



BUILDING SERVICE CONTRACTORS



MUNICIPALITIES

## TECHNICAL DATA

	CT40 BT50
Code	
<b>PERFORMANCE</b>	
Max theoretical productivity	2250 m <sup>2</sup> /h
Cleaning path	500 mm
Water tank capacity (solution recovery)	40/50 l
Max running time	140 min
Voltage	24(2x12)-105 GEL V-Ah
Installed power	1250 W
Brush pressure	18 kg
Squeegee width	815 mm
Max speed	4,5 km/h
Weight	73 kg
Dimension (LxWxH)	1230 x 516 x 960 mm

## CONSUMABLES (Codes available on price list)

### BRUSHES



SPPV01498 | POLYPROPYLENE (PP) BRUSH

### PADS



L-17260 | 20' POLISH PAD - WHITE  
 L-17261 | 20' BUFF PAD - RED  
 L-17262 | 20' SCRUB PAD - BLUE  
 L-1243339 | 20' BUFF PAD - RED (BOX OF 5)  
 L-1243352 | 20' POLISH PAD - WHITE (BOX OF 5)

### SQUEEGEE BLADES



MPVR08039 | LATEX FRONT BLADE  
 MPVR08035 | LATEX REAR BLADE

IPC Australia  
 Unit 11, 4 Southridge Street  
 Eastern Creek NSW 2766

T: 1800 226 843 (FREE CALL)  
 T: +61 2 9839 9700

E: [contactanz@ipcworldwide.com](mailto:contactanz@ipcworldwide.com)  
 W: [www.ipcworldwide.com](http://www.ipcworldwide.com)

IPC New Zealand  
 Unit 5, 103 Cryers Road  
 East Tamaki  
 Auckland 2013

T: +64 9 253 9013  
 F: +64 9 253 9015