



STEAM GENERATORS

SG-70

(ONLY STEAM - 50l WATER TANK)

PRESSURE

9 bar

FLOW RATE

330 g/min

ABSORBED POWER

11,4 kW



EXCLUSIVE CHARACTERISTICS

- ▶ POWER BOILER
- ▶ ANTI BUGS
- ▶ POWER FILTER
- ▶ AUTOMATIC SHUTDOWN
- ▶ SAFETY
- ▶ ERGONOMICS
- ▶ POWER FLEX
- ▶ DURABILITY

MOST FREQUENTLY USE

AUTOMOTIVE

HO.RE.CA.


FOOD INDUSTRY AND RETAILERS

LARGE COMMON AREAS

INNOVATIONS



SPECS



STAINLESS STEEL STRUCTURE



ERGONOMIC HANDLE



STAINLESS STEEL - STORAGE COMPARTMENT

TECHNICAL DATA

SG-70 9536 T 400V

Code	GNVA40042	
PERFORMANCE		
Operating pressure	bar/Mpa	9/0,9
Steam flow rate	g/min	~330
Steam temperature (max)	°C	180
Start up time	min	~ 10
Power supply	Ph-V-Hz/A	3-400-50/16,3
Absorbed power max.	kW	11,4
Boiler volume	l	16
Water tank	l	50
Detergent tank	l	6
Dimension (LxWxH)	cm	115x65x100
Weight	Kg	167,20

STANDARD EQUIPMENT

CODE: IPIP40016
HANDGRIP + HOSE STEAM
10 m (ONLY HANDGRIP
CODE: IPIP40015)



CODE: LCPR40109
STEAM LANCE 1/4 - F INOX



CODE: UGEI40012
STEAM NOZZLE 1/4F -
INOX



OPTIONAL ACCESSORIES

CODE: SPPV40051
RECTANGULAR BRUSH -
L300 mm



CODE: UGLN40037
STEAM NOZZLE 1/4F
PLATE



CODE: LCPR40165
CURVED STEAM LANCE
L=250 mm M22 - (FOR
RECTANGULAR BRUSH)



CODE: LCPR40166
CURVED STEAM LANCE
L=450 mm M22 - (FOR
RECTANGULAR BRUSH)



CODE: LCPR40167
CURVED STEAM LANCE
L=1050 mm M22 - (FOR
RECTANGULAR BRUSH)



CODE: LCPR40111
CURVED STEAM LANCE
L=450 mm M22 + 1/4 M -
(FOR STEAM NOZZLE)



CODE: LCPR40130
CURVED STEAM LANCE
L=1050 mm M22 + 1/4 M -
(FOR STEAM NOZZLE)



CODE: LCPR40108
STEAM LANCE L=250 mm
M22 + 1/4M
(FOR STEAM NOZZLE)



CODE: LCPR40110
STEAM LANCE L=450 mm
M22 + 1/4M
(FOR STEAM NOZZLE)



CODE: LCPR40112
STEAM LANCE L=900 mm
M22 + 1/4M
(FOR STEAM NOZZLE)



CODE: LCPR40113
STEAM LANCE L=1050 mm
M22 + 1/4M - (FOR STEAM
NOZZLE)



CODE: APTA40024
REGENERATION STATION

