



GS 2/50 FM OPT OIL

EXCLUSIVE FEATURES

- ▶ MODERN INDUSTRIAL DESIGN
- ▶ FLOWMIX SYSTEM TO ACTIVATE DOUBLE VACUUM SUCTION
- ▶ BIG RUBBER WHEELS WITH BRAKES, EASY TO MOVE IN LARGE AREAS
- ▶ SIEVE BASKET TO SEPARATE ABRASIVE/CUTTING SOLIDS MIXED WITH LIQUIDS
- ▶ 2 HIGH VELOCITY MOTORS WITH TOP PERFORMANCES
- ▶ BEST SEALING OF THE POWERHEAD THANKS TO EXCLUSIVE BUILT-IN GASKET
- ▶ VISUAL FILLING INDICATOR AND DRAIN VALVE
- ▶ METAL TANGENTIAL INLET SEALED TO CREATE CYCLONIC EFFECT AND AVOID LEAKAGES

GS 2/50 FM OPT OIL

Code	ASD013655	
TECHNICAL DATA		
Usage	WET & DRY	
Number of phases	single phase	
Voltage / Frequency	V	220-240/50-60
N. and type of motor	2 x single stage HV	
Power	W	2200 - 2600 max
Water lift	mmH ₂ O	2380 FM OFF / 3800 FM ON
Airflow	m ³ /h	400 FM OFF / 220 FM ON
Tank Capacity	l	50
Diameter of inlet	mm	60
Filtering surface	cm ²	2960
Sound Pressure Level	dB(A)	72
Dimensions (LxWxH)	mm	580x700x1150
Weight	Kg	45

STANDARD EQUIPMENT

CODE: MPVR10591
INTERNAL RING



CODE: FTDP00285
WASHABLE POLYESTER
CARTRIDGE 2.960 cm²



CODE: SECC00187
BUCKET SIEVE 30 L



CODE: FTDP28755
MESH FILTER



CODE: MPVR28723
FIXING SYSTEM FOR
MESH FILTER AND
CARTRIDGE



OPTIONAL ACCESSORIES

Complete multipurpose premium tool kit 3 m ø38 mm	PMDT01227
Complete multipurpose premium tool kit 4 m ø50 mm	PMDT01228
Complete Oil&Abrasives Tool kit 4 m Ø38 mm	PMDT00928
Anti-oil tool kit for inlet ø60 mm	PMDT00447



PLANET OIL 3M

EXCLUSIVE FEATURES

- ▶ INDEPENDENT MOTORS WITH LIGHT SWITCHES
- ▶ DRAIN HOSE
- ▶ RELIABLE CONSTRUCTION FOR INTENSIVE USE
- ▶ DETACHABLE TANK AND SOLID CART
- ▶ TANGENTIAL OR METAL INLET
- ▶ DOUBLE STAGE MOTORS AND TURBINE
- ▶ BIG AND BRAKED WHEELS
- ▶ QUICK MAINTENANCE FRAMEWORK WITH DETACHABLE TANK
- ▶ SIEVE BASKET & ANTI BLOCK FLOATING SYSTEM
- ▶ ANTISKID WHEELS WITH BRAKES
- ▶ VISUAL FILLING INDICATOR
- ▶ SAFETY VALVES AND DRAIN SYSTEM
- ▶ INDUSTRIAL FRAMEWORK WITH AISI 304 WITH DETACHABLE TANK
- ▶ TANGENTIAL INLET AND CONVEYOR CONE
- ▶ VACUUM RELIEF VALVE AND FILTRATION LEVEL INDICATOR

PLANET OIL 3M

Code	ASID00524	
TECHNICAL DATA		
Usage	WET & DRY	
Number of phases	single phase	
Voltage / Frequency	V	220-240/50-60
N. and type of motor	3 x 2 stages	
Power	W	3600 - 3800 max
Water lift	mmH ₂ O	2795
Airflow	m ³ /h	630
Tank Capacity	l	100
Diameter of inlet	mm	60
Filtering surface	cm ²	3100+1500
Sound Pressure Level	dB(A)	76
Dimensions (LxWxH)	mm	850x650x1350
Weight	Kg	65

STANDARD EQUIPMENT

CODE: KTRI02521
FILTERING KIT
(3100 + 1500 cm²)



CODE: FTCC00011
NYLON FILTER (PA 200 µ)



CODE: SECC00113
BUCKET SIEVE 40 L



OPTIONAL ACCESSORIES

Anti-oil tool kit Ø50-60 mm	PMDT00449
Pre separator kit 2" y connector for tank filling	KTRI05973