



VACUUM CLEANERS - SPECIAL SOLUTIONS - FLOODED AREA EMPTYING

# GS 2/62 SUB

POWER MAX

2400  
W

WATER LIFT

2470  
mmH<sub>2</sub>O

AIRFLOW

420  
m<sup>3</sup>/h

TANK CAPACITY

62  
l



PUMP  
OUT

## EXCLUSIVE FEATURES

- ▶ AP TUBE
- ▶ INNOVATIVE GASKET
- ▶ STRONG HOOKS
- ▶ INDEPENDENT MOTORS WITH LIGHT SWITCHES
- ▶ SEALANT FLOATER & INTEGRATED ANTI-FOAM SYSTEM
- ▶ RELIABLE CONSTRUCTION FOR INTENSIVE USE
- ▶ SUBMERSIBLE PUMP
- ▶ DOUBLE STAGE MOTORS

## MOST FREQUENTLY USE

AGRICULTURE



CONSTRUCTION



HARDWARE CUSTOMER



HEAVY INDUSTRY



AUTOMOTIVE



## INNOVATIONS



## SPECS



PROFESSIONAL SUBMERSIBLE PUMP



INTEGRATED ANTI-FOAM SYSTEM



ELECTRIC POWER SOCKET ON BOARD (FOR PUMP)

## TECHNICAL DATA

		<b>GS 2/62 SUB</b>
Code		ASD015119
<b>PERFORMANCE</b>		
Usage		WET
Motor		2x2 stage
Power	W	2400 max
Voltage	V	220-240
Water lift	mmH <sub>2</sub> O	2470
Airflow	m <sup>3</sup> /h	420
Tank Capacity/Material	l	62/steel
Cable length	m	8,5
Sound Pressure Level (EN 60704-1; EN 60704-2-1; IEC 60335-2-69)	dB(A)	77
Pump type		Plastic
Pump power	W	370
Pump capacity	l/min	180
Solids diameter for pumping out	mm	20 max
Delivery head	m	7
Diameter of accessories	mm	38
Dimensions (LxWxH)	mm	550x600x960
Weight	kg	21,0

## STANDARD EQUIPMENT

### PMDT00350 ACCESSORIES KIT FOR SUB Ø38 MM COMPOSED OF:

CODE: TBFX28237  
FLEXIBLE HOSE 2,5 m  
Ø38 mm



CODE: LAFN43048 (FOR 1 PC)  
ALUMINIUM/PLASTIC  
TUBE 50 cm Ø38 mm  
(MACHINE COMES WITH 2PCS)



CODE: MPVR43047  
HANDLE WITH AIR  
REGULATOR Ø38 mm



CODE: SPPV43051  
WET TOOL Ø38 mm



## OPTIONAL ACCESSORIES

CODE: TBBP00719  
ANTIFREEZE HOSE 5 m  
Ø30 mm



CODE: FSVR00129  
HOSE CLAMP 30X45



CODE: PMVR06680  
DFS POLY KIT



To connect to water flow valve