



PLANET 201 HEPA

Available 60Hz version

EXCLUSIVE FEATURES

- ▶ INDEPENDENT MOTORS WITH LIGHT SWITCHES
- ▶ RELIABLE CONSTRUCTION FOR INTENSIVE USE
- ▶ DETACHABLE TANK AND SOLID CART
- ▶ MULTI STAGE FILTRATION
- ▶ DOUBLE STAGE MOTORS AND TURBINE
- ▶ BIG AND BRAKED WHEELS
- ▶ INDUSTRIAL FRAMEWORK WITH AISI 304 WITH DETACHABLE TANK
- ▶ STARSHAPED FILTER, PCB PREFILTER AND ADDITIONAL CARTRIDGE
- ▶ VACUUM RELIEF VALVE AND FILTRATION LEVEL INDICATOR
- ▶ HEPA H13 CARTRIDGE AND FILTERS SURFACE AREA
- ▶ RESISTANT FRAMEWORK AND INLET PLUG FOR SAFE TRANSFER

PLANET 201 HEPA
ASID00411

Code		PLANET 201 HEPA	
TECHNICAL DATA		ASID00411	
Usage		DRY	
Number of phases		single phase	
Voltage	V	220-240	
Frequency	Hz	50-60	
N. and type of motor		3x2 stages	
Power	W	3600 - 3800 max	
Water lift	mmH ₂ O	2795	
Airflow	m ³ /h	630	
Tank Capacity/Material	l	40	
Diameter of inlet	mm	60	
Filtering surface	cm ²	25000	
Sound Pressure Level	dB(A)	76	
Dimensions (LxWxH)	mm	740x660x1100	
Weight	Kg	65	

STANDARD EQUIPMENT

CODE: KTRI04597
FILTERING KIT



CODE: PMVR06189
COMPLETE CAP FOR INLET
(FOR SAFE DISPOSAL)



CODE: FTDP40014
POLYCARBON PREFILTER



CODE: FTDP00359
HEPA H13 CARTRIDGE
8340 cm²



OPTIONAL ACCESSORIES

Basic tool kit Ø50-60 mm	PMDT00443
Anti-Static tool kit Ø50-60 mm	PMDT00436
Star-shaped high temperature filter	KTRI04595



PLANET 200S PLANET 200 TS

Available 60Hz version

EXCLUSIVE FEATURES

- ▶ INDEPENDENT MOTORS WITH LIGHT SWITCHES
- ▶ RELIABLE CONSTRUCTION FOR INTENSIVE USE
- ▶ DETACHABLE TANK AND SOLID CART
- ▶ MANUAL FILTER SHAKER
- ▶ TANGENTIAL OR METAL INLET
- ▶ DOUBLE STAGE MOTORS AND TURBINE
- ▶ BIG AND BRAKED WHEELS
- ▶ INDUSTRIAL FRAMEWORK WITH AISI 304 WITH DETACHABLE TANK
- ▶ TANGENTIAL INLET AND CONVEYOR CONE
- ▶ STARSHAPED FILTER, PCB PREFILTER AND ADDITIONAL CARTRIDGE
- ▶ VACUUM RELIEF VALVE AND FILTRATION LEVEL INDICATOR
- ▶ NON-SLIP NYLON WHEELS WITH BRAKES

PLANET 200S **PLANET 200 TS**
ASID00390 ASID89596

Code		PLANET 200S		PLANET 200 TS	
TECHNICAL DATA		ASID00390		ASID89596	
Usage		DRY		DRY	
Number of phases		single phase		single phase	
Voltage	V	220-240		220-240	
Frequency	Hz	50-60		50-60	
N. and type of motor		3x2 stages		3x3 stages	
Power	W	3600-3800 max		4500 max	
Water lift	mmH ₂ O	2795		3260	
Airflow	m ³ /h	630		485	
Tank Capacity	l	100		100	
Diameter of inlet	mm	70		70	
Filtering surface	cm ²	19.500		19.500	
Sound Pressure Level	dB(A)	76		76	
Dimensions (LxWxH)	mm	660x900x1630		660x900x1630	
Weight	kg	70		70	

STANDARD EQUIPMENT

CODE: KTRI04597
FILTERING KIT



CODE: FTDP40014
POLYCARBON PREFILTER



OPTIONAL ACCESSORIES

Basic tool kit Ø50-70 mm	PMDT00444
Anti-Static tool kit Ø50-70 mm	PMDT00426
Anti-oil tool kit Ø50-70 mm	PMDT00448
Stainless steel float kit to recovery liquid (for Planet 100 lt)	KTRI03124
Hepa cartridge H13 kit 8.340 cm ²	FTDP00800
Fixed accessory floor cleaning	SPPV49605
Steel grid and depressor kit for bag use	KTRI02498
Star-shaped high temperature filter	KTRI04595