



PNEUMATIC/
AIR OPERATED



PLANET 300S PN ATEX

CE EX II 3D Ex t IIIB T135°C Dc IP55

CARATTERISTICHE ESCLUSIVE

- ▶ RELIABLE CONSTRUCTION FOR INTENSIVE USE
- ▶ DETACHABLE TANK AND SOLID CART
- ▶ MANUAL FILTER SHAKER
- ▶ TANGENTIAL OR METAL INLET
- ▶ FILTER OVERPRESSURE INDICATORS
- ▶ EXPLOSION PROOF TURBINE AND DESIGN FOR ATEX ZONE 22
- ▶ STATIC DISSIPATING FILTERS
- ▶ PCB PREFILTER AND ADDITIONAL CARTRIDGE
- ▶ GROUNDING SYSTEM

PLANET 300 S PN ATEX

ASID00293

Codice

TECHNICAL DATA

Usage		DRY
Air consumption	l/min	700-1300
Air pressure	bar	6
Water lift	mmH ₂ O	2200-3300
Air flow	m ³ /h	330
Tank capacity	l	100
Diameter of inlet	mm	70
Dimensions (LxWxH)	mm	630 x 890 x 1650
Weight	kg	72

ACCESSORI STANDARD

CODICE: KTRI04594
CONDUCTIVE
FILTERING KIT



CODICE: FTDP40014
POLYCARBON PREFILTER



CODICE: FTDP00375
POLYESTER CARTRIDGE
10.000 cm²



ACCESSORI OPZIONALI

Anti-static kit tools for inlet Ø50-70 mm	PMDT00426
Stainless steel float kit to recovery liquid (for Planet 100 lt)	KTRI03124
Reusable conductive bag ATEX (for Planet 100 lt)	KTRI03175
Retainer plate with clip (for conductive bag)	PWR00190
High reach cleaning ATEX	AVAILABLE