



IPC

BY TENNANT COMPANY

EXCLUSIVE CHARACTERISTICS

- ▶ DELAYED TOTAL STOP - DTS
- ▶ INTELLIGENT AUTOMATIC SWITCH OFF - IASF
- ▶ MICRO LEAKAGE CONTROL - MLC
- ▶ DRY RUNNING PROTECTION - DRP
- ▶ LANCE NOZZLE CLOGGED CONTROL - NCC
- ▶ WORKING HOURS COUNTER - WHC
- ▶ LIMESCALE/CORROSION PROTECTION UNIT - LCPU
- ▶ INTELLIGENT BOILER TEMPERATURE SETTING SYSTEM - ITSS
- ▶ ANTI-SCALE LEVEL CONTROL - ALC
- ▶ CHEMICAL LEVEL CONTROL - CLC
- ▶ FLOODING PREVENTION SYSTEM - FPS
- ▶ MAINTENANCE CHECK LED - MCL

MOST FREQUENTLY USE

INDUSTRY



AUTOMOTIVE



AGRICULTURE



MUNICIPALITIES



HIGH-PRESSURE WASHERS - HOT WATER (ELECTRIC BOILER)

PW-E101

PRESSURE

170
bar

FLOW RATE

600÷720
l/h

ABSORBED POWER

16÷37,5
kW



WITH NO-MARKING RUBBER WHEELS

INNOVATIONS



AMSC™
ADVANCED
MULTIFUNCTION
SAFETY CONTROL



CIRCULAR
DESIGN
& OPERATION



IPC
PUMP



DIGITAL
DISPLAY
DD



IPC'S
EXCLUSIVE
BOILER



G6000™
CERAMIC
HIGH-TECH GUN



ALL
TERRAIN



MODERN
MODULAR
BUILD-UP

SPECS



LARGE WHEELS IMPROVE
MANEUVERABILITY AND EASE
TRANSPORT



CONTROL PANEL WITH
INDICATOR LAMPS AND
DISPLAY



3 STAGE HIGH EFFICIENCY
BOILER WITH AISI 316
STAINLESS STEEL STRUCTURE

TECHNICAL DATA

Code		PW-E101 D1710 P12 T IDAC41400	PW-E101 D1710P17 T IDAC41630	PW-E101 D1712 P24 T IDAC41401	PW-E101 D1712 P36 T IDAC41403
PERFORMANCE					
Operating pressure	bar/Mpa	30-170/3-17	30-170/3-17	30-170/3-17	30-170/3-17
Flow rate	l/h	450-600	450-600	450-720	450-720
Outlet water temperature	°C	80	80	80	80
Power supply	Ph-V-Hz/A	3-400-50/25	3-400-50/31	3-400-50/41,8	3-400-50/55,9
Absorbed power	kW	15,9	20,8	28,2	37,5
Motor pole/rpm		4-1400	4-1400	4-1400	4-1400
Remote control		DTS	DTS	DTS	DTS
Pump/head/pistons		lpc plunger/brass/ceramic	lpc plunger/brass/ceramic	lpc plunger/brass/ceramic	lpc plunger/brass/ceramic
Boiler thermal power	kW	12	17	24	36
Antiscale tank	l	25	25	25	25
Detergent tank	l	22	22	22	22
Detergent delivery		high pressure	high pressure	high pressure	high pressure
Dimension (LxWxH)	cm	110x70x90	110x70x90	110x70x90	110x70x90
Weight	Kg	126,2	126,2	125,2	129,6

STANDARD EQUIPMENT

CODE: IPPR40025
HANDGRIP G6000



CODE: LCPR40087
EXTENSION P70 INOX



CODE: TBAP40237
NO-MARKING H.P HOSE
10 m 1/4"



CODE: UGLN49986
H.P. NOZZLE 1/4" 1504 -
(FOR 24kW/ 36kW)



CODE: UGLN11196
H.P. NOZZLE 1/4" 15035 -
(FOR 12KW AND 17KW)



OPTIONAL ACCESSORIES

CODE: LCPR29360
MUDGUARD LANCE - P90



CODE: LCPR24906
LANCE WITH DOUBLE
NOZZLE HOLDER - P70



CODE: SPID24939
FIXED HYDROBRUSH
LANCE P70



CODE: LCLC41140
LANCE FOR WASHING
FLOORS INOX



CODE: TBAP23853
DRAIN KIT 10 m



CODE: TBAP24406
DRAIN KIT 20 m



CODE: KTRI40341
HOSE REEL KIT



CODE: TBAP39122
NO-MARKING HIGH
PRESSURE HOSE 20 m



CODE: PRCH40040
10 Kg ANTI-SCALE TANK



CODE: KTRI40686
REMOTE CONTROL



**OPTIONAL ACCESSORY
HAS TO BE INSTALLED
DURING MANUFACTURING
PROCESS**