



PW-H101 HTM



PRESSURE

200 bar

FLOW RATE

ABSORBED POWER

 $900\,\mathrm{l/h}$

6,4 kW

EXCLUSIVE CHARACTERISTICS

- DELAYED TOTAL STOP DTS
- INTELLIGENT AUTOMATIC SWITCH OFF - IASF
- MICRO LEAKAGE CONTROL-MLC
- DRY RUNNING PROTECTION DRP
- NOZZLE CLOGGED CONTROL - NCC
- IGNITION BOILER DELAY IBD
- WORKING HOURS COUNTERWHC
- LIMESCALE/CORROSION PROTECTION UNIT - LCPU
- DIGITAL TEMPERATURE STABILIZER CONTROL - DTSC
- ANTISCALE LEVEL CONTROL-ALC
- FUEL LEVEL CONTROL FLC
- ► INFRARED FLAME CONTROL SYSTEM FCS
- MAINTENANCE CHECK LED MCL



PW-H101 HTM

SPECIAL MACHINE: 100°C MAX TEMPERATURE, BOTH HIGH AND LOW PRESSURE MODE

(WITH NO-MARKING RUBBER WHEELS / 3 WHEELS VERSION)

MOST FREQUENTLY USE



CONSTRUCTION

CONSTRUCTION

RETAIL

LOGISTICS AND TRANSPORT

INDUSTRY

COMMUNITIES

WASTE MANEGEMENT

INNOVATIONS



AMSC™ ADVANCED MULTIFUNCTION SAFETY CONTROLS

HIGH-TECH GUN

G6000TM

CERAMIC



CIRCULAR DESIGN & OPERATION

TERRAIN





MODERN

MODULAR

BUILD UP

DIGITAL DISPLAY DD





ANTI-SCALE

SPECS



WARNING LAMP INFORMS WHEN TEMPERATURE IS BETWEEN 90-100°C



BOILER CAN BE OPENED FROM THE TOP FOR AN EASY CLEANING



COMPLETE WITH NON MARKING WHEELS FOR FLAT SURFACED (3 WHEELS VERSIONS)

TECHNICAL DATA 3 wheels

PW-H101HT D2015P T Code IDAC41394 4 wheels PW-H101/4HT D2015P T Code IDAC41395

PERFORMANCE		
Operating pressure	bar/Mpa	30-200/3-20
Flow rate	l/h	450-900
Outlet water temperature	°C	100
Power supply	Ph-V-Hz/A	3-400-50/13
Absorbed power	kW	6,4
Motor pole/rpm		4-1400
Remote control		DTS
Pump/head/pistons		lpc plunger/brass/ceramic
Boiler thermal power	kW	100
Fuel consumption	kg/h	7,4
Fuel tank	l	25
Detergent tank	l	22
Detergent delivery		high pressure
Dimension (LxWxH)	cm	110x70x90
Weight	kg	140

STANDARD EQUIPMENT

CODE: IPPR40029 **HANDGRIP G6000** WITH CERAMIC VALVE CODE: LCPR40191 **EXTENSION PD70 cm** INOX

CODE: UGLN05200 H.P. NOZZLE 1/4 1505 CODE: UGLN07790 L.P. NOZZLE 1/4 2513 CODE: TBAP40237 H.P. HOSE 10MT 1/4" (NO-MARKING)











OPTIONAL ACCESSORIES

CODE: KTRI40341 **HOSE REEL KIT**



CODE: RCIN10810 **HOSE COUPLING M22**



CODE: LCLC41140 LANCE FOR WASHING **FLOORS INOX**



CODE: LCLC40027 STAINLESS STEEL FLOOR



LANCE WITHOUT NOZZLES. **USE: NO. 2 CODE: UGLN49988** THAT SHOULD BE ORDERED **SEPARATELY**

CODE: PRCH40039 ANTISCALE TREATMENT M4211Kg X6



CODE: UGLN49988 H.P. NOZZLE 1/4 25025



CODE: PRCH40040 ANTISCALE TREATMENT M42110 Kg



CODE: KTRI40568 **MAINTENANCE KIT 500H**

