



IPC

BY TENNANT COMPANY

HIGH-PRESSURE WASHERS - HOT WATER

PW-H101 PREMIUM

PRESSURE

200÷250
bar

FLOW RATE

900÷1300
l/h

ABSORBED POWER

7,5÷8,5
kW

EXCLUSIVE CHARACTERISTICS

- ▶ DELAYED TOTAL STOP - DTS
- ▶ INTELLIGENT PROPORTIONAL SWITCH OFF - IPSF
- ▶ MICRO LEAKAGE CONTROL - MLC
- ▶ DRY RUNNING PROTECTION - DRP
- ▶ LANCE NOZZLE CLOGGED CONTROL - NCC
- ▶ IGNITION BOILER DELAY - IBD
- ▶ WORKING HOURS COUNTER - WHC
- ▶ FLOODING PREVENTION SYSTEM - FPS
- ▶ FUEL LEVEL CONTROL - FLC
- ▶ LIMESCALE/CORROSION PROTECTION UNIT - LCPU
- ▶ ANTISCALE LEVEL CONTROL - ALC
- ▶ DIGITAL TEMPERATURE STABILIZER CONTROL - DTSC
- ▶ MAINTENANCE CHECK LED - MCL
- ▶ INFRARED FLAME CONTROL SYSTEM - FCS
- ▶ LED INDICATOR LIGHT REACHING TEMPERATURE TL



PW-H101
PREMIUM

PW-H101/4
PREMIUM

MOST FREQUENTLY USE

AUTOMOTIVE



AGRICULTURE



CONSTRUCTION INDUSTRY



MUNICIPALITIES



HEAVY INDUSTRY



INNOVATIONS



AMSC™
ADVANCED
MULTIFUNCTION
SAFETY CONTROL



DIAD
DIRECT INJECTION
DETERGENT AND
ANTI-SCALE



DIGITAL
DISPLAY
DD



IPC
PUMP



G6000™
CERAMIC
HIGH-TECH GUN



ALL
TERRAIN



MODERN
MODULAR
BUILD-UP



IPC'S
EXCLUSIVE
BOILER

SPECS



CONTROL PANEL WITH
INDICATOR LAMPS AND
DISPLAY



BOILER CAN BE OPENED
FROM THE TOP FOR AN EASY
CLEANING



EASILY ACCESSIBLE
ANTISCALE TANK

TECHNICAL DATA

3 wheels

Code

4 wheels

Code

PERFORMANCE

		PW-H101P D2021P T IDAC41387	PW-H101P D2515P T IDAC41388
		PW-H101/4P D2021P T IDAC41391	PW-H101/4P D2515P T IDAC41392
Operating pressure	bar/Mpa	30-200	30-250/3-25
Flow rate	l/h	650-1300	450-900
Outlet water temperature	°C	30-140	30-140
Power supply	Ph-V-Hz/A	3-400-50/15,9	3-400-50/15
Absorbed power	kW	8,1	7,5
Motor pole/rpm		4-1400	4-1400
Remote control		DTS	DTS
Pump/head/pistons		lpc plunger/brass/ceramic	lpc plunger/brass/ceramic
Boiler thermal power	kW	≤100	≥70
Fuel consumption	kg/h	7,7	5,9
Fuel tank	l	25	25
Detergent tank	l	22	22
Detergent delivery		high pressure	high pressure
Dimension (LxWxH)	cm	110x70x90	110x70x90
Weight	kg	167	162,4

STANDARD EQUIPMENT

CODE: IPPR40025

H.P. HOSE R1 10M 5/16"



CODE: LCPR40159

EXTENSION P70 INOX 0°



CODE: UGLN49986

H.P. NOZZLE 1/4 1504
(FOR 2515)



CODE: UGLN02303

H.P. NOZZLE 1/4 15065
(FOR 2021)



CODE: TBAP40256

HIGH PRESSURE HOSE 10 m
(FOR 2021)



CODE: TBAP40309

HIGH PRESSURE HOSE 10 m
(FOR 2515)



CODE: -

ANTI-SCALE TREATMENT
M421 1 Kg



OPTIONAL ACCESSORIES

CODE: LCPR29360

MUDGUARD LANCE - P90



CODE: LCPR24906

LANCE WITH DOUBLE
NOZZLE HOLDER - P70



CODE: SPID24939

FIXED HYDROBRUSH
LANCE P70



CODE: LCLC41140

LANCE FOR WASHING
FLOORS INOX



CODE: LCPR14860

SANDBLASTER KIT Ø 1,7 mm
(FOR 2021)



CODE: LCPR14858

SANDBLASTER KIT Ø 1,4 mm
(FOR 2515)



CODE: PRCH40041

SAND BAG 25 Kg



CODE: TBAP24406

DRAIN KIT 20 m
(FOR 2021)



CODE: LCPR40103

EXTENSION P70 + TPR255
Ø0,4 (FOR 2515)



CODE: LCPR40171

EXTENSION P70 + R.J.255
Ø0,65 (FOR 2021)



CODE: LCPR29363

STEAM LANCE - P70



CODE: KTRI40341

HOSE REEL KIT



CODE: PRCH40039

ANTI-SCALE TREATMENT
M421 1 Kg X6



CODE: PRCH40040

ANTI-SCALE TREATMENT
M421 10 Kg



CODE: KTRI40647

MAINTENANCE KIT 500H
(FOR 2021)



CODE: KTRI40648

MAINTENANCE KIT 500H
(FOR 2515)



CODE: KTRI40669

HOSE REEL KIT ON BOARD



IP Cleaning Srl Viale Treviso 63 - 30026 Summaga di Portogruaro (VE) - Italy

Tel. +39 0421 205511 - Fax +39 0421 204227 | info@ipcworldwide.com - www.ipcworldwide.com